

HOT AND COLD ROLLED STRIPS

NASTRI LAMINATI A CALDO E A FREDDO

PRODUCT RANGE - HOT ROLLED STRIPS 1D

Gamma produttiva - Nastri laminati a caldo 1D

thickness mm	width mm
3	from 40 up to 1500
4	from 40 up to 1500
5	from 40 up to 1500
6	from 40 up to 1500

PRODUCT RANGE - COLD ROLLED STRIPS 2B

Gamma produttiva - Nastri laminati a freddo 2B

thickness mm	width mm
0,8	from 35 up to 1500
1	from 35 up to 1500
1,2	from 35 up to 1500
1,5	from 35 up to 1500
2	from 35 up to 1500
2,5	from 35 up to 1500
3	from 35 up to 1500
4	from 35 up to 1500

MANUFACTURING STANDARD <i>Norma di fabbricazione</i>	FINISH <i>Finitura</i>	PRODUCT DESIGNATION <i>Designazione prodotto</i>	GRADE <i>Qualità</i>			
EN 10088-2 ASTM A240, A480	1D Annealed and pickled <i>Ricotto e decapato</i>	Stainless steel flat products for general purposes <i>Acciai inossidabili piani per impieghi generali</i>	Austenitic	<i>Austenitici</i>	Ferritic	<i>Ferritici</i>
			EN 1.4307 1.4404	AISI 304L 316L		
	2B Annealed pickled and skinpassed <i>Ricotto, decapato e skinpassato</i>		Austenitic	<i>Austenitici</i>	Ferritic	<i>Ferritici</i>
			EN 1.4307 1.4404	AISI 304L 316L	EN 1.4512 1.4510 1.4509	AISI 409Li 439L 441
EN 10088-4 (CE marking)	1D Annealed and pickled <i>Ricotto e decapato</i>	Stainless steel flat products for construction purposes <i>Acciai inossidabili piani per impieghi strutturali</i>	Austenitic	<i>Austenitici</i>	Ferritic	<i>Ferritici</i>
			EN 1.4307 1.4404	AISI 304L 316L		
	2B Annealed pickled and skinpassed <i>Ricotto, decapato e skinpassato</i>		Austenitic	<i>Austenitici</i>	Ferritic	<i>Ferritici</i>
			EN 1.4307 1.4404	AISI 304L 316L	EN 1.4512 1.4510 1.4509	AISI 409Li 439L 441
EN 10028-7 ASTM A240, A480 (AD 2000 W2/W10) (PED 2014/68/EU)	1D Annealed and pickled <i>Ricotto e decapato</i>	Stainless steel flat products for pressure purposes <i>Acciai inossidabili piani per recipienti a pressione</i>	Austenitic	<i>Austenitici</i>		
			EN 1.4307 1.4404	AISI 304L 316L		
	2B Annealed pickled and skinpassed <i>Ricotto, decapato e skinpassato</i>		Austenitic	<i>Austenitici</i>		
			EN 1.4307 1.4404	AISI 304L 316L		

Supply conditions - *Condizioni di fornitura*

- Dimensional tolerances according to EN ISO 9445-2 (and other equivalent international norms)
Tolleranze dimensionali secondo norma EN ISO 9445-2 (e altre norme internazionali equivalenti)

- Special tolerances upon request *Tolleranze speciali su richiesta*



4 slitting line

50,000 t/y
total manufacturing
capacity hot rolled
and cold rolled strips